



MILITARY UNIQUE DEPLOYMENT GUIDE

6.1.2 | November 2017 | 3725-03137-005A

Polycom® RealPresence® Group Series for Maximum Security Environments



Copyright© 2017, Polycom, Inc. All rights reserved. No part of this document may be reproduced, translated into another language or format, or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of Polycom, Inc.

6001 America Center Drive
San Jose, CA 95002
USA

Trademarks Polycom®, the Polycom logo and the names and marks associated with Polycom products are trademarks and/or service marks of Polycom, Inc. and are registered and/or common law marks in the United States and various other countries.



All other trademarks are property of their respective owners. No portion hereof may be reproduced or transmitted in any form or by any means, for any purpose other than the recipient's personal use, without the express written permission of Polycom.

Disclaimer While Polycom uses reasonable efforts to include accurate and up-to-date information in this document, Polycom makes no warranties or representations as to its accuracy. Polycom assumes no liability or responsibility for any typographical or other errors or omissions in the content of this document.

Limitation of Liability Polycom and/or its respective suppliers make no representations about the suitability of the information contained in this document for any purpose. Information is provided "as is" without warranty of any kind and is subject to change without notice. The entire risk arising out of its use remains with the recipient. In no event shall Polycom and/or its respective suppliers be liable for any direct, consequential, incidental, special, punitive or other damages whatsoever (including without limitation, damages for loss of business profits, business interruption, or loss of business information), even if Polycom has been advised of the possibility of such damages.

End User License Agreement BY USING THIS PRODUCT, YOU ARE AGREEING TO THE TERMS OF THE END USER LICENSE AGREEMENT (EULA) AT: <http://documents.polycom.com/indexes/licenses>. IF YOU DO NOT AGREE TO THE TERMS OF THE EULA, DO NOT USE THE PRODUCT, AND YOU MAY RETURN IT IN THE ORIGINAL PACKAGING TO THE SELLER FROM WHOM YOU PURCHASED THE PRODUCT.

Patent Information The accompanying product may be protected by one or more U.S. and foreign patents and/or pending patent applications held by Polycom, Inc.

Open Source Software Used in this Product This product may contain open source software. You may receive the open source software from Polycom up to three (3) years after the distribution date of the applicable product or software at a charge not greater than the cost to Polycom of shipping or distributing the software to you. To receive software information, as well as the open source software code used in this product, contact Polycom by email at OpenSourceVideo@polycom.com.

Customer Feedback We are striving to improve our documentation quality and we appreciate your feedback. Email your opinions and comments to DocumentationFeedback@polycom.com.

Polycom Support Visit the [Polycom Support Center](#) for End User License Agreements, software downloads, product documents, product licenses, troubleshooting tips, service requests, and more.

Contents

Deployment Guide for Maximum Security Environments	5
Document Change History	5
FIPS 140-2 Cryptography	6
Locate Your System	6
Configuring Your System	6
Preparing for Configuration	7
Installation in a Non-DHCP Environment	7
Installation on a Network Using 802.1X	7
Installing Certificates	7
Installing Software Options	7
Install the Software	7
Configuring Initial Settings Using the Setup Wizard	8
Configure Localization and System Name	8
Configure LAN Settings	9
Configure Security Settings	10
Configure Certificates	10
Revoke Certificates	11
Completing the Configuration	11
Configure Time Services	12
Configure Numeric Keypad Function Settings	12
Configure Home Screen Settings	12
Configure Active Directory Server Settings	13
Configure Local Access Controls and SNMP	13
Configure Call Media Encryption	14
Configure the PC LAN Port	14
Configure IP Network Settings	14
Configure Dial Preference Settings	16
Configure Log Management	16
Configure Local Password Policy	16
Update Your System Using Provisioning	20
Configure Enterprise Network Services	20
Using the System	20
View Network Interface and System Status	21
Collecting Log Files	21

Use the Camera Privacy Cover 21
SD Memory Card Deep Erase with USB Factory Restore 22
Conditions of Fielding 22

Deployment Guide for Maximum Security Environments

This guide provides guidance for configuring and using software version 6.1.2 to be consistent with the conditions for deployment as listed in the UC APL listing for Polycom® RealPresence® Group Series systems, Polycom® RealPresence Centro™ systems, Polycom® RealPresence® Resource Manager, and Polycom® RealPresence® Medialign™. For a listing of certified software versions, refer to the Polycom [Government Certification & Accreditation](#) website.



Note: This software, when configured per the guidance provided in this guide, is designed to meet the latest U.S. Department of Defense (DoD) security requirements for listing on the Unified Capabilities (UC) Approved Products List (APL) as maintained by the Defense Information Systems Agency (DISA) Unified Capabilities Connection Office (UCCO).

For more information about the UC APL process, please visit the [UCCO website](#).

In the configuration sections of this document, if a setting is mandated by a DISA Security Technical Implementation Guide (STIG) requirement, the specific STIG reference is listed along with the setting.

Document Change History

This information is required for listing on the US Department of Defense (DoD) Unified Capabilities (UC) Approve Products List (APL).

Document Version	Build Number	Certification Date	Description
1.0	GS 4.1.0_J and RPRM 7.3.0J	February 2014	Initial certification with Redcom for Group Series and RealPresence Resource Manager
2.0	GS 4.1.5	April 2015	DTR1 – Updated features, added fixes, addressed POA and Ms
3.0	GS 4.1.5	April 2015	DTR2 – Shift GS to AEI listing after testing with NEC
4.0	GS 4.3.0	July 2015	DTR3 – Updated GS features and added fixes

Document Version	Build Number	Certification Date	Description
5.0	GS 4.3.2	October 2015	DTR4 – Added Polycom RealPresence Group Series 310 (GS 310) and Polycom® EagleEye™ camera (EEP)
6.0	GS and Centro 5.1.2	October 2016	DTR5 – Updated GS features, added fixes, and added Centro platform
7.0	RPRM 10.0.1	October 2016	DTR 6- Updated RPRM to 10.0.1
N/A	GS and Centro 5.1.2, RPRM 10.0.1	September 2017	DTR7 - Certification and CRADA Extension
8.0	GS, Centro, Medialign 6.1.2, RPRM 10.1 appliance and Virtual Edition	November 2017	DTR8 - Updated GS features and fixes, added Medialign and RPRM Virtual Edition

To request information or submit comments about this document, please contact [Polycom Global Services](#).

FIPS 140-2 Cryptography

Polycom RealPresence Group Series software uses OpenSSL FIPS Object Module (Software Version: 2.0). This module provides FIPS-140-approved cryptography for the system. The validation certificate for this module can be found at the [Validated FIPS 140-1 and FIPS 140-2 Cryptographic Modules](#) web page.

Locate Your System

The system should be placed in a secured location and on a firewall-protected network segment.

Configuring Your System

The following sections describe how to manually configure system settings to meet the DoD security requirements.

- [Preparing for Configuration](#)
- [Install the Software](#)
- [Configuring Initial Settings Using the Setup Wizard](#)
- [Completing the Configuration](#)
- [Update Your System Using Provisioning](#)
- [Configure Enterprise Network Services](#)

For detailed information about configuring your system, see *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0* at [Polycom Support](#).

Preparing for Configuration

To have everything you need to configure the system, consider the following conditions and if they apply, follow their guidance prior to beginning.

Installation in a Non-DHCP Environment

If you are installing the RealPresence Group Series system in a non-DHCP environment, you must manually configure the local area network (LAN) properties during the setup wizard using the local interface and the remote control, so be sure to have the LAN information ready.

Installation on a Network Using 802.1X

If you are installing the RealPresence Group Series system on a network that uses 802.1X, you have the following choices:

- Complete the setup wizard using the local interface and the remote control so you can enter the 802.1X credentials, which then allows the system to connect to the network.
- Connect the system to a local network that does not use 802.1X so you can use the web interface to complete the setup wizard. After you complete the wizard settings and enter the 802.1X credentials, you can connect the system to the network that uses 802.1X authentication.

Installing Certificates

To configure the system to use certificates or to customize other settings, you must access the RealPresence Group Series system web interface using a computer located on the same network segment as the RealPresence Group Series system.

Installing Software Options

If you purchased software options for your RealPresence Group Series system, be sure to activate the software option licenses and get the corresponding software option “key codes” that activate the options on your system before you start installation. Store these key codes in a license file called `sw_keys.txt`. To do this, follow the instructions in *Installing Software and Options for the Polycom RealPresence Group Series and Accessories*.

Install the Software

If your system did not come with version 6.1.2 already installed, you must download and install the RealPresence Group Series 6.1.2 software. The recommended procedure is to use the USB factory restore operation because it removes the previous version of software and any settings and data that accompanied it, installs the 6.1.2 software, and starts the system at the setup wizard where you can reconfigure the system from the beginning.

To install software version 6.1.2 using USB factory restore:

- 1 Download the 6.1.2 software from the **Polycom UC APL Certified Software** section of the Polycom [Government Certification and Accreditation](#) website.
- 2 Using the downloaded software file, follow the instructions in the “Using a USB Device for a Factory Restore” section of the *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0*. Polycom recommends invoking the optional “Zeroize” procedure on any system that has been previously deployed.

After the software is installed, the system runs the setup wizard.



Note: The RealPresence Group Series system requires two USB ports to update the software as well as the camera. For instructions on how to perform a factory restore using USB storage devices to install a specific software version, see the *Polycom RealPresence Group Series Administrator Guide* at [Polycom Support](#).

Configuring Initial Settings Using the Setup Wizard

The following sections describe how to use the setup wizard to meet the DoD security requirements:

- [Configure Localization and System Name](#)
- [Configure LAN Settings](#)
- [Configure Security Settings](#)
- [Configure Certificates](#)
- [Revoke Certificates](#)

For detailed information about configuring your system, see *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0* at [Polycom Support](#).

Configure Localization and System Name

The first few settings in the setup wizard enable you to select the language you want to use, along with the country and system name.

To configure language, location, and system name settings:

- 1 Choose the language that you want to use, accept the End User License Agreement, then select the **Advanced** setup.
- 2 Select your country.
- 3 Choose a **System Name**. Since RealPresence Group Series systems use the configured System Name as the default DNS host name, choose a name that is a valid DNS host name. Per RFC 1123, valid host names have the following characteristics:
 - Names are 1 to 63 characters long.
 - Names can consist of letters a through z (case-insensitive), numbers 0 through 9, and the hyphen character (-).

- Host names cannot start or end with a hyphen.



Note: You can enable your RealPresence Group Series system to be provisioned by a Polycom® RealPresence® Resource Manager system. If you do so, use the same name for system name and DNS host name that the RealPresence Resource Manager system will provision to the RealPresence Group Series endpoint. That name will be registered within the local DNS server. Failing to use this naming scheme could lead to PKI certificate validation problems and communication failures that sometimes result when a host name changes but the PKI certificates, which contain the host name, have previous host name information.

Configure LAN Settings

These settings apply to your local area network (LAN).

To configure the LAN settings:

- 1 If the network uses 802.1X:
 - a Select **Enable EAP/802.1X**.
 - b Configure the **Identity** and **Password** fields with the credentials assigned to the RealPresence Group Series system.
- 2 If the network uses 802.1p/Q:
 - a Select **Enable 802.1p/Q**.



Note: If you are installing a RealPresence Group Series 700 system and need to use the PC LAN port, you might need to enable 802.1Q VLAN tagging to ensure that the data coming from the RealPresence Group Series endpoint can be tagged and separated from the data coming from any device connected to the PC LAN port. Consult with your local network administrators for guidance.

- b Enter the **VLAN ID** of the virtual LAN assigned to be used by the RealPresence Group Series system.
 - c Configure the 802.1p Class of Service (COS) values for **Video Priority**, **Audio Priority**, and **Control Priority** per the local network COS policy.
- 3 Choose the IP address assignment mode (IPv4):
 - a If DHCP is to be used, select **Obtain IP address automatically** in the IP address menu to automatically populate the remaining fields.
 - b If manual address assignment is to be used, select **Enter IP address manually** in the IP address menu and then enter the assigned IP address in the **Your IP Address is** field, along with the **Default Gateway** address and the **Subnet Mask**.
- 4 If the system is also to use IPv6:
 - a Select **Enable IPv6**.
 - b If DHCPv6 or SLAAC is to be used, select **Obtain IP address automatically** in the IP address (IPv6) menu to automatically populate the remaining fields.
If DHCPv6 is available on the network, disable **Enable SLAAC**. Otherwise, leave the setting enabled.
 - c If manual address assignment is used, select **Enter IP address manually** in the IP address menu, and then enter the assigned IP addresses along with the address of the **Default Gateway**.

Configure Security Settings

These settings control the defaults for the level of security you want on your RealPresence Group Series system and the passwords needed to use the system.

To configure security settings:

- 1 Set the Security Profile to **Maximum**.



Note: Configuring the software to use the Maximum security profile ensures that the system operates in compliance with DoD UCR 2013 Change 1 requirements. The use of other profiles and configurations is allowed, but the onus in these modes for compliance with DoD security requirements then falls on the RealPresence Group Series system administrator. Only the Maximum security profile is guaranteed to place the RealPresence Group Series endpoint into a compliant posture by default.

- 2 Set the **Admin ID** to a value other than `admin`.
- 3 Set an **Admin Room Password** and an **Admin Remote Access Password** that meet the default password policy for the Maximum security profile as described in the *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0*.
- 4 Set the **User ID** to a value other than `user`.
- 5 Set a **User Room Password** and a **User Remote Access Password** that meet the default password policy for the Maximum security profile as described in the *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0*.

Configure Certificates

Certificates are digital documents exchanged between servers to ensure secure communication. These settings control how those digital documents are created and exchanged.

To configure certificates:

- » Do one of the following:
 - If the RealPresence Group Series endpoint is being deployed in an environment that *does not* use PKI, disable the **Always Validate Peer Certificates from Browser** and **Always Validate Peer Certificates from Server** settings.
No other settings changes are required. The RealPresence Group Series system uses its default self-signed certificate for all web interface access and client certificate challenges.
 - If the RealPresence Group Series endpoint is being deployed in an environment that *does* use PKI:
 - 1 Set the **Maximum Peer Certificate Chain Depth** to the depth of the largest trust hierarchy that the RealPresence Group Series endpoint will encounter when attempting to validate an identity certificate from a remote device.
 - 2 Create both a client CSR and a server CSR and then have them signed by the CA that issues certificates for the particular PKI within your environment. See the detailed instructions in the *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0*.
 - 3 Install the signed client and server certificates into the RealPresence Group Series system using the **View and Add** link on the Certificates page.

- 4 Install all CA certificates needed to validate certificates from any remote device the RealPresence Group Series system connects to.
- 5 Make sure the **Always Validate Peer Certificates from Browser** and **Always Validate Peer Certificates from Server** settings are selected.

Revoke Certificates

You must maintain the certificates you use by regularly verifying their validity and ensuring that expired certificates are revoked. You can use the OSCP or CRL method of revocation.

Polycom strongly recommends that you use OCSP as the revocation mechanism because it provides automated online checking of certificate status and does not require manual installation of CRLs.

To use the OCSP method:

- 1 Choose **OCSP** as the **Revocation Method** (this is the default choice).
- 2 For **Global Responder Address**, configure the address of an OCSP Responder that can be used to check revocation status for any certificate that does not have an AIA field populated.
- 3 Select **Use Responder Specified in Certificate** if the CAs used in the PKI support populating the AIA field with their responder address.
- 4 Disable **Allow Incomplete Revocation Checks** to ensure that revocation checks are always made even if a temporary network outage prevents the RealPresence Group Series system from contacting an OCSP responder. Otherwise, enable this setting.

To use the CRL method:

- 1 Choose **CRL** as the **Revocation Method**.
- 2 Click **Add CRL** to load a CRL for each CA that might be part of the trust chain for a certificate that the RealPresence Group Series system receives and has to validate. Note that you must keep these CRLs up to date manually to ensure that connection failures don't result because an expired CRL was loaded.
- 3 Enable **Allow Incomplete Revocation Checks** if you want to allow revocation checking to be skipped if no CRL is loaded for a CA that is part of a certificate's trust chain (Polycom does not typically recommend this setting). Otherwise, disable this setting.
- 4 Complete the rest of the setup wizard as desired.

Completing the Configuration

After you complete the setup wizard and the system restarts, you are ready to finish the initial system configuration. The following sections describe this configuration.

- [Configure Time Services](#)
- [Configure Numeric Keypad Function Settings](#)
- [Configure Home Screen Settings](#)
- [Configure Active Directory Server Settings](#)
- [Configure Local Access Controls and SNMP](#)
- [Configure Call Media Encryption](#)

- [Configure the PC LAN Port](#)
- [Configure IP Network Settings](#)
- [Configure Dial Preference Settings](#)
- [Configure Log Management](#)
- [Configure Local Password Policy](#)

Configure Time Services

These settings allow the RealPresence Group Series system to synchronize its internal clock with a network time server using Network Time Protocol (NTP).

To configure Time Services:

- 1 Log in to the system's web interface using the new admin ID and admin remote access password that you set.
- 2 Go to **Admin Settings > General Settings > Date and Time > System Time**.
- 3 Set the **Time Zone** to the time zone where the system is physically located.
- 4 Set the **Time Server** to **Manual**.
- 5 Set the **Primary Time Server Address** to the address of the NTP server designated as the primary server.
- 6 Set the **Secondary Time Server Address** to the address of the NTP server designated as the secondary server, if one is available.

Configure Numeric Keypad Function Settings

These settings control the behavior of the system when placing, receiving, or participating in a call.

To configure the Numeric Keypad Function settings:

- 1 Go to **Admin Settings > General Settings > System Settings > Remote Control, Keypad, and Power**.
- 2 Configure the **Numeric Keypad Function** setting.
If you plan to use the local camera presets, leave this setting at its default (**Presets**). If you don't intend to use camera presets or users need to be able to enter digits into Inbound Voice Response (IVR) systems during calls, select **Tones** for this setting. A user might need to enter digits when using a Polycom® RealPresence® Collaboration Server for gateway calling, selecting a conference room within an entry queue, entering conference passwords, and so forth.

Configure Home Screen Settings

These settings control what information is shown on your system's home screen on the local interface both in and out of calls.

- 1 Go to **Admin Settings > General Settings > Home Screen Settings > Address Bar**.
- 2 Configure the following settings.

Setting	Description
Address Bar (Left Element)	Allows you to select which element you want displayed on the left side of the address bar on the local interface. The choices are: <ul style="list-style-type: none"> • None • IP Address • H.323 Extension • Pairing Code
Address Bar (Right Element)	Allows you to select which element you want displayed on the right side of the address bar on the local interface. The choices are: <ul style="list-style-type: none"> • None • IP Address • H.323 Extension • Pairing Code

Configure Active Directory Server Settings

These settings connect your system to the Active Directory server used to authenticate local user access to the system. If your system does not use an Active Directory Server, you can skip this step.

- 1 Go to **Admin Settings > Security > Global Security > Authentication**.
- 2 Select the **Enable Active Directory External Authentication** setting.
- 3 Configure the other Active Directory settings according to the guidance in the “External Authentication” section of the *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0*.



Note: When you enable External Authentication, the local user account is disabled, so the **User ID**, **User Room Password**, and **User Remote Access Password** settings are not used.

Configure Local Access Controls and SNMP

These settings control who can access your system and how it can be accessed.

To configure the local access control and SNMP:

- 1 Go to **Admin Settings > Security > Global Security > Access**.
- 2 Enable or disable the **Allow Access to User Settings** setting per your local site guidelines.
- 3 If you plan to use SNMP, select **Enable SNMP Access** and then configure the SNMP settings per your site requirements and the guidance provided in the “Set Up SNMP” section of the *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0*.

- 4 To limit web interface and SNMP access to a list of only known IP addresses, select the **Enable Whitelist** setting.

Edit the whitelist to add the IP address of the workstation you are currently using. Doing so prevents your workstation from being locked out when you apply the changes. If you plan to use SNMP, include the IP addresses of any SNMP consoles that need to access the system.

- 5 Configure the **Idle Session Timeout in Minutes** setting per your local site guidelines as needed.

Configure Call Media Encryption

RealPresence Group Series systems use the Advanced Encryption Standard (AES) for call encryption. AES is a Federal Information Processing Standard (FIPS) Publication (FIP-197) that specifies a cryptographic algorithm for use by U.S. Government organizations to protect sensitive and unclassified information.

To configure encryption:

- 1 Go to **Admin Settings > Security > Global Security > Encryption**.
- 2 Configure the **Require AES Encryption for Calls** setting per your local site guidelines.
Polycom recommends that, for interoperability purposes, you use the **When Available** setting because it always uses encryption when available.

Configure the PC LAN Port

Only RealPresence Group 700 systems have a PC LAN port on the back of the system. Configure this port to enable Ethernet use.

To configure the PC LAN port:

- 1 Go to **Admin Settings > Network > LAN Properties > LAN Options**.
- 2 Configure the **Enable PC LAN Port** setting, based on whether its use is required.



Note: If you do enable the **Enable PC LAN Port** setting, be sure to also configure the **Enable 802.1p/Q** settings per your local site guidelines.

Configure IP Network Settings

These settings control the types of networks your system uses, as well as gatekeeper, network quality, and firewall settings.

For general guidance, on how to configure IP settings, see the *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0* at [Polycom Support](#).

To configure the IP network settings:

- 1 Go to **Admin Settings > Network > IP Network**.
- 2 Set up the following:
 - Click **H.323** to display the H.323 settings. Select **Enable H.323** if H.323 calling is required. If you enable H.323, configure the other H.323 settings as needed.
 - Click **SIP** to display the SIP settings. Select **Enable SIP** if SIP calling is required. Select **AS-SIP** if AS-SIP calling is required.
 - ◆ If you enable SIP, configure the other SIP settings as needed. Select **TLS** as the **Transport Protocol** to guarantee that only secured signaling is used.
 - ◆ If you enable SIP, the **Force Connection Reuse** option is disabled by default. This causes the RealPresence Group Series system to use an ephemeral source port for all outgoing SIP messages. When this option is enabled, the RealPresence Group Series system uses the

active SIP listening port as the source port (5060 or 5061, depending on the negotiated SIP transport protocol in use). Enabling this option is beneficial when you need to establish correct operation with remote SIP peer devices that require that the source port match the contact port in SIP messages.

- ◆ If you enable AS-SIP, configure the SIP Registrar and Proxy server addresses to point to the *local session controller (LSC)*, and then configure the AS-SIP-specific settings as required. An LSC is the AS-SIP call server in an AS-SIP deployment. It is used by the RealPresence Group Series system as both the SIP registrar and proxy server.

3 If you enabled AS-SIP, click **AS-SIP** to display the AS-SIP settings. You might find the following information helpful:

- The default Network Domain (**Default Domain**) assigned to the system is **uc**. You can set it to any of the configured network domains.
- The default outgoing call precedence level (**Default Precedence**) is **ROUTINE**. You can change it to any precedence level defined within the configured **Default Domain**.
- The system is pre-configured for use on both the **uc** and **dsn** network domains, with default precedence levels and associated DSCP values for audio and video traffic per UCR 2013 Change 1. If these defaults do not apply to your deployment, you can change them. For details, see *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0* at [Polycom Support](#).



Note: If you enable AS-SIP and have the TIP option installed, go to **Admin Settings > Network > Dialing Preference** and disable the **TIP** setting. TIP signaling and AS-SIP signaling are incompatible with each other.

4 Click **Quality of Service** to configure the appropriate settings on the IP Network page.

Setting	Description
Type of Service	Configure this setting to match the type of IP Quality of Service tagging being used on the network to which the system is connected. If there is no QoS tagging on the network, leave the setting at IP Precedence and the other Type of Service settings at their default values. If AS-SIP is enabled, select Diffserv .
Video	Configure this setting with the IP Precedence or Diffserv DSCP value intended for video traffic. If AS-SIP is enabled, set to 36 . This is the value for video in non-AS-SIP calls (regular SIP or H.323 calls). AS-SIP calls take their video DSCP value from the AS-SIP network domain configuration settings.
Audio	Configure this setting with the IP Precedence or Diffserv DSCP value intended for audio traffic. If AS-SIP is enabled, set to 34 . This is the value for audio in non-AS-SIP calls (regular SIP or H.323 calls). AS-SIP calls take their audio DSCP value from the AS-SIP network domain configuration settings.

Setting	Description
Control	Configure this setting with the IP Precedence or Diffserv DSCP value intended for call control traffic. If AS-SIP is enabled, set to 40 .
OA&M	Configure this setting with the IP Precedence or Diffserv DSCP value intended for operations, administration, and management (OA&M) traffic. If AS-SIP is enabled, set to 16 .

Configure Dial Preference Settings

These settings control how calls are placed on systems that have multiple call protocols enabled.

To configure dialing preferences:

- 1 Go to **Admin Settings > Network > Dialing Preference > Dialing Options**.
- 2 Configure the **Video Dialing Order**:
 - Select **IP H.323** to place calls using H.323 first.
 - Select **SIP** to place calls using SIP first.

Configure Log Management

These settings control how system log information is stored on your system.

To configure log management:

- 1 Go to **Admin Settings > Security > Log Management**.
- 2 Configure these settings on the Log Management screen if periodic transfer of logs to an attached USB storage device is required.

Setting	Description
Percent Filled Threshold	<ul style="list-style-type: none"> • Specifies the percentage of the log file space that, when consumed, triggers a system alert. It can also trigger an automatic transfer of logs to an attached USB storage device if that setting is enabled. Suggested value: 70. • This alert is mandated by the Application Security STIG (APP3650 in V3R3).
Transfer Frequency	Set this to Auto at Threshold to enable periodic transfer of logs to an attached USB storage device Set this to Manual to disable periodic transfer of logs to an attached USB storage device

- 3 If remote log storage is required, go to **Diagnostics > System > System Log Settings** to select the **Enable Remote Logging** setting, and then configure the **Remote Log Server Address** as needed.

Configure Local Password Policy

The use of *strong* passwords (defined as passwords containing a sufficient number and diversity of character types, such as uppercase letters, lowercase letters, numbers, and special characters) is

recommended for security purposes. It is prudent, however, to keep in mind that strong room passwords require the use of the onscreen virtual keyboard to enter letters and special characters. This requirement can make it possible for others to view a password as you enter it. You can mitigate this risk by using longer numeric-only passwords that you can enter using the remote control. You can also mitigate this risk by using a USB keyboard connected to the RealPresence Group Series system through the USB port.



Note: Support for the USB keyboard is specifically to enter complex login information such as for Active Directory accounts. For all other system interaction, use the remote control.

The following tables give guidance for password policy settings that are compliant with U.S. DoD security requirements. If a setting is mandated by a Defense Information Systems Agency (DISA) Security Technical Implementation Guide (STIG) requirement, the specific STIG reference is listed along with the setting.

To configure your local password policy:

- 1 Go to **Admin Settings > Security > Local Accounts > Password Requirements**, and configure the following settings.
 - If you are not using an external Active Directory Server, also configure the following settings for the User Room password.
 - If you are using SNMPv3, also configure the following settings for the SNMP passwords, as applicable.

Setting	Strong Passwords	Numeric-only Passwords
Minimum Length	Value: 15 (recommended) This setting meets these requirements: <ul style="list-style-type: none"> • Red Hat Enterprise Linux 6 STIG V1R8: RHEL-06-000050 (minimum 14) • Application Security and Development Checklist V3R10: APP3320 (minimum 15) • DSN STIG V2R6: DSN13.06 (minimum 8) • GR-815-CORE-2 R3-39 [26] (minimum 6) • DODI 8500.2: IAIA-1, IAIA-2 (minimum 8) • VTC STIG V1R6: RTS-VTC 2024.00 (minimum 6) 	Value: 15
Require Lowercase Letters	Value: 1 (2 for Remote Access) This setting meets these requirements: <ul style="list-style-type: none"> • Red Hat Enterprise Linux 6 STIG V1R8: RHEL-06-000059 • Application Security and Development Checklist V3R10: APP3320 • DSN STIG V2R6: DSN13.06 • GR-815-CORE-2 R3-39 [26] • DODI 8500.2: IAIA-1, IAIA-2 	Off

Setting	Strong Passwords	Numeric-only Passwords
Require Uppercase Letters	Value: 1 (2 for Remote Access) This setting meets these requirements: <ul style="list-style-type: none"> Red Hat Enterprise Linux 6 STIG V1R8: RHEL-06-000057 Application Security and Development Checklist V3R10: APP3320 DSN STIG V2R6: DSN13.06 GR-815-CORE-2 R3-39 [26] DODI 8500.2: IAIA-1, IAIA-2 	Off
Require Numbers	Value: 1 (2 for Remote Access) This setting meets these requirements: <ul style="list-style-type: none"> Red Hat Enterprise Linux 6 STIG V1R8: RHEL-06-000056 Application Security and Development Checklist V3R10: APP3320 DSN STIG V2R6: DSN13.06 GR-815-CORE-2 R3-39 [26] DODI 8500.2: IAIA-1, IAIA-2 	All
Require Special Characters	Value: 1 (2 for Remote Access) This setting meets these requirements: <ul style="list-style-type: none"> Red Hat Enterprise Linux 6 STIG V1R8: RHEL-06-000058 Application Security and Development Checklist V3R10: APP3320 DSN STIG V2R6: DSN13.06 GR-815-CORE-2 R3-39 [26] DODI 8500.2: IAIA-1, IAIA-2 	Off

2 Configure the following settings.

Setting	Description
Reject Previous Passwords	Value: 10 This setting meets these requirements: <ul style="list-style-type: none"> • Application Security and Development Checklist V3R10: APP3320 (requires 10) • DSN STIG V2R6: DSN13.09 (requires 8) • GR-815-CORE-2: R3-38 [25] (requires 5) • VTC STIG V1R6: RTS-VTC 2040.00 (requires 8)
Minimum Password Age in Days	Value: 1 or Off This setting meets these requirements: <ul style="list-style-type: none"> • Application Security and Development Checklist V3R10: APP3320 (minimum 1 for users, 0 for administrators) • DSN STIG V2R6: DSN13.08 (minimum 1 without IAO intervention) • GR-815-CORE-2: R3-38 [25] (minimum 20) • Red Hat Enterprise Linux 6 STIG V1R8: RHEL-06-000051 (minimum 1)
Maximum Password Age in Days	Value: 60 This setting meets these requirements: <ul style="list-style-type: none"> • Red Hat Enterprise Linux 6 STIG V1R8: RHEL-06-000053 (maximum 60) • Application Security and Development Checklist V3R10: APP3320 (maximum 60) • DSN STIG V2R6: DSN13.07 (maximum 90) • GR-815-CORE-2: R3-33 [21] (maximum 20-90)
Minimum Changed Characters	Value: 4 This setting meets these requirements: <ul style="list-style-type: none"> • DODI 8500.2: IAIA-1, IAIA-2 • Red Hat Enterprise Linux 6 STIG V1R8: RHEL-06-000060 • Application and Security Checklist V3R10: APP3320
Maximum Consecutive Repeated Characters	Value: 3 This setting meets this requirement: <ul style="list-style-type: none"> • Red Hat Enterprise Linux 6 STIG V1R8: RHEL-06-000299
Password Expiration Warning	Value: 7 This setting meets these requirements: <ul style="list-style-type: none"> • GR-815-CORE-2: CR3-36 [23] • Red Hat Enterprise Linux 6 STIG V1R8: RHEL-06-000054 (requires 7)
Can Contain ID or Its Reverse Form	Disable This setting meets these requirements: <ul style="list-style-type: none"> • GR-815-CORE-2: R3-39 [26] • Application Security and Development Checklist V3R10: APP3320

Update Your System Using Provisioning

Provisioning is a way to automatically or manually apply software updates to your RealPresence Group Series systems.

To provision a RealPresence Group Series system from the RealPresence Resource Manager:

- 1 Ensure that the RealPresence Resource Manager system has been configured to operate in Maximum Security Mode.
- 2 Create site, user group, and bundled profiles that are to be used to provision your RealPresence Group Series system. Make sure they are consistent with your local deployment policies and with the configuration guidance of this document.
- 3 Configure your RealPresence Group Series system as previously described in this document. Refer to the steps in [Install the Software](#), [Configuring Initial Settings Using the Setup Wizard](#), and [Completing the Configuration](#) for more information.
- 4 After completing the configuration in this document, configure your RealPresence Group Series system to use a provisioning service as described in the “Use a Provisioning Service” section of the *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0*. This allows the RealPresence Group Series system to be in a proper state for accepting provisioning information from the RealPresence Resource Manager when both systems are using their Maximum security configurations.

Configure Enterprise Network Services

Enterprise network services control your directory server.

To configure enterprise network services:

- 1 Go to **Admin Settings > Servers > Directory Servers**.
- 2 If an LDAP directory server is available, select **LDAP** for the **Server Type** setting.
- 3 Configure the rest of the LDAP directory server configuration settings per the guidance in the *Polycom RealPresence Group Series Administrator Guide* associated with the software version running on the RealPresence Group Series system. Note the following:
 - You can use the RealPresence Resource Manager server as the LDAP directory server (recommended), or you can use an Active Directory server.
 - Select the **Use SSL (Secure Socket Layer)** setting to guarantee secure connections to the directory server.

Using the System

If you have completed the steps leading up to this section of the document, your RealPresence Group Series system is ready for use within your maximum security environment. The following is information you might find helpful as you use your system.

View Network Interface and System Status

You can view the **System Status** screen on the local interface or by using the RealPresence Group Series web interface. The **System Status** screen displays system status information, including auto answer point-to-point, IP network, meeting password, and log threshold.

To view the system status in the local interface:

- » Go to **System > Status**.

To view the System Status using the RealPresence Group Series system web interface:


- 1 Open a web browser, and in the browser address line enter the system IP address, for example, `https://10.11.12.13`, to go to the RealPresence Group Series system web interface.
- 2 Enter the user ID for an admin account (either the local admin account or an Active Directory account that is part of the Admin Group) and the associated password.
- 3 After you have successfully logged in, click **Diagnostics > System > System Status** from any page in the RealPresence Group Series system web interface.
- 4 For an explanation of any of the status items, click the **More Info** link.

Collecting Log Files

The RealPresence Group Series endpoint supports both local storage and offload of system log files (via either an attached USB storage device or via the RealPresence Group Series system web interface), as well as the use of remote storage via a Syslog server. For more information, see the *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0* at [Polycom Support](#).

Use the Camera Privacy Cover

The Polycom® EagleEye™ camera goes to sleep when the RealPresence Group Series system does. For added security, Polycom offers a privacy cover (part number 2215-28454-001) that you can attach to the camera. You can open and close the cover as needed. Contact your Polycom distributor for more information.



SD Memory Card Deep Erase with USB Factory Restore

You can perform a "deep erase" of the system SD memory card by invoking the "Zeroize" procedure as part of a USB factory restore. This procedure erases all evidence and artifacts of the system's previous use in such a way that even a manual analysis of the SD memory card cannot retrieve information that resided there prior to the deep erase. This is important when deploying the system in highly sensitive environments.

To perform this operation, follow the instructions for using a USB Device for a factory restore" in the *Polycom RealPresence Group Series Administrator Guide, Version 6.1.0* at [Polycom Support](#) and choose to add the optional "Zeroize" procedure.

Conditions of Fielding

CONDITION OF FIELDING. When the system is deployed into an operational environment, the following security measures (at a minimum) must be implemented to ensure an acceptable level of risk for the sites' Designated Approving Authority:

a. The system must be incorporated in the site's PKI. If PKI is not incorporated, the following findings will be included in the site's architecture:

Application Security and Development Checklist:

APP3305, CAT 1, for RealPresence Resource Manager

APP3280, CAT II, for RealPresence Resource Manager

APP3290, CAT II, for RealPresence Resource Manager

APP3300, CAT II, for RealPresence Resource Manager

Application Services Checklist:

APS0110, CAT II, for RealPresence Resource Manager

Defense Switched Network (DSN):

DSN13.17, CAT II (x6), for RealPresence Centro; RealPresence Group Series (GS300, GS310, GS500, GS700); RealPresence Resource Manager

Network Checklists:

NET0445, CAT II (x6), for RealPresence Centro; RPGS (GS300, GS310, GS500, GS700);
RealPresence Resource Manager

- b.** The site must use role-based security for user access and management of the vendor's device.
- c.** The system must be integrated into the site's AD environment for normal user access, authentication, and authorization requirements.
- d.** The site must disable all local user accounts on the device after initial setup/configuration with the exception of one emergency administrative account.
- e.** The site must ensure that the emergency administrative account's userid and password are locked up in separate safes, both of which are not accessible by any one individual, and procedures are implemented to log all access and usage.
- f.** The site must ensure that the emergency administrative account meets all DoD userid and password complexity requirements.
- g.** The site must ensure all unused ports are closed.
- h.** The site must use a STIG-compliant CAC-enabled workstation for management of the solution.
- i.** The configuration must be in compliance with the *Polycom RealPresence Group Series Family Release 6.1.2 Military-Unique Deployment Guide*.
- j.** The site must register the system in the Systems Networks Approval Process Database <https://snap.dod.mil/index.cfm> as directed by the DSAWG and Program Management Office.
- k.** The site must configure the video endpoints to **Encrypt All Calls**.